

Dust Containment PREMIUM SHROUDS

FULL SHROUD 05-65710 HINGED SHROUD 05-65713

Use the Blastrac Premium Shrouds as part of the dust containment system on hand grinders, sanders or polishers to help reduce airborne dust and particulates. The Shroud facilitates a cleaner and safer work environment when grinding, planing, or removing coatings from concrete.

The shroud's unique snail shape design uses the velocity of air created by the rotating grinding wheel to force air to travel in a cyclone fashion, thus creating higher centrifugal force which expels the dust particles away from the grinding wheel up into the hose port. This technology improves removal of particles which further improves the grinding process.

When coupled with the BDC-1112EU or BDC-1216 dust collector, and equipped with the Blastrac premium shroud, the 05-67000 operates with nearly all dust eliminated. The operator can breathe easier while observing the work area more safely, increasing job productivity.

The Premium Shrouds are easy to install, no tools required, and are designed to fit 7" and 9", 15 amp grinders. Inserts are included to fit Blastrac, DeWalt, Milwaukee, Hitachi, and Metabo grinders.



Inserts are included to fit Blastrac, DeWalt, Milwaukee, Hitachi and Metabo grinders.

FEATURES AND BENEFITS:

- Utilizes cyclone dust-extraction technology
- Attaches easily with no tools
- Reinforced with steel ring embedded in perimeter and for close-up work next to walls and other vertical protrusions
- Insert rings (included) allow shroud to fit models of these other popular grinders:
 - DeWalt
 - Milwaukee
 - Hitachi
 - Metabo

Blastrac offers a variety of application specific diamond cup wheels and grinding disks.

SPECIFICATIONS:

Dust Hose Connection: 2 in. (50.8mm)
Dimensions:
 L 9.75 in. x W 8.5 in. x H 4 in.
 (L 248mm x W 216mm x H 102mm)
Weight: 1.375 lb. (0.624kg)



*Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collector.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.

Products manufactured and marketed by Blastrac are protected by patents issued or pending in the United States and other countries. Blastrac reserves the right to change the specifications referred to in this literature at any time, without prior notice. Blastrac is a registered trademark owned by Blastrac, NA.

The Trusted Choice of Professionals for Over 30 Years



1.800.256.3440 • BLASTRAC.com

© 2015 Blastrac, NA All rights reserved. V0215.